

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
21 July 2005 (21.07.2005)

PCT

(10) International Publication Number
WO 2005/067160 A1

(51) International Patent Classification⁷: **H04B 1/69**,
H04L 27/00

(21) International Application Number:
PCT/SG2004/000006

(22) International Filing Date: 6 January 2004 (06.01.2004)

(25) Filing Language: English

(26) Publication Language: English

(71) Applicant (for all designated States except US): **AGENCY
FOR SCIENCE, TECHNOLOGY AND RESEARCH**
[SG/SG]; 20 Biopolis Way #07-01, Centros, Singapore
138668 (SG).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **TAN, Eng, Choon,**
Adrian [MY/SG]; Blk 169 Boon Lay Drive #09-665, Sin-
gapore 640169 (SG). **CHIA, Yan, Wah, Michael** [SG/SG];
Blk 5 Rivervale Crescent #02-04, Singapore 545084 (SG).

(74) Agent: **POH, Chee, Kian, Daniel**; Lloyd Wise, Tanjong
Pagar, P.O. Box 636, Singapore 910816 (SG).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.


(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), Euro-
pean (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR,
GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK,
TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,
ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:

— of inventorship (Rule 4.17(iv)) for US only

[Continued on next page]

(54) Title: METHOD OF GENERATING UWB PULSES



(57) Abstract: A method produces UWB pulses (73, 75) using a differentiated clock signal as a pulse input (71, 72), and a data signal to modulate the pulse input. The mixed signal is then differentiated a second time to produce high frequency broad band UWB signals. A differentiating system which comprises a transistor, a lowpass filter at the output of the transistor, the output of the lowpass filter negatively feedback to the input of the transistor, whereby the output of system has a high voltage swing capable of being matched to an antenna without further need of amplification, and the system is capable of implementation on an IC.

WO 2005/067160 A1



Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.